

Data sheet

Text Display TD 03 (603-1TD00)

Technical data

Order no.	603-1TD00
Type	Text Display TD 03
General information	
Note	-
Features	Display: 2 x 20 characters Interface: MP2I Languages: DE, EN Visualization of the connected CPU via MPI Project engineering via TD-Wizard of VIPA
Display	
Number of rows	2
Characters per row	20
Character height	5 mm
Type of display	STN with LED backlighting
OP functionality	
User memory	-
Number of variables	-
Language	DE/EN
Operating controls	
Touchscreen	-
Keyboard	Membran keyboard
Mouse	-
Number of system keys	5
Number of soft keys	4
Technical data power supply	
Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	80 mA
Current consumption (rated value)	500 mA
Inrush current	16 A
I _{2t}	0.11 A²s
Time	
Real-time clock	-
Clock buffered period (min.)	-
Accuracy (max. deviation per day)	-
Functionality Sub-D interfaces	
Type	MP2I
Type of interface	RS485
Connector	Sub-D, 9-pin, female
Electrically isolated	-
MPI	yes
MP2I (MPI/RS232)	yes
Point-to-point interface	-

5V DC Power supply max. 90mA, non-isolated

24V DC Power supply -

Mechanical data

Housing / Protection class

Material die-cast aluminum

Mounting via integrated pivoted lever

Protection class IP front side IP 65

Protection class IP back side IP 20

Protection class NEMA front side -

Protection class NEMA back side -

Dimensions

Front panel 187 mm x 90 mm x 6 mm

Rear panel 154 mm x 77 mm x 44 mm

Installation cut-out

Width 156 mm

Height 78 mm

Minimum 2.5 mm

Maximum front panel thickness 6 mm

Net weight 610 g

Weight including accessories -

Gross weight -

Environmental conditions

Operating temperature 0 °C to 60 °C

Storage temperature -20 °C to 70 °C

Certifications

UL certification yes

KC certification -